## MKCT TYPE OIL SIGNAL INCLUDED IN THE FRAME

- This product is the flow sight which confirms the flow of a fluid by motion of the float in a transparent tube.
- Since this product is protected with a metal protection cover, it does not almost have fear of breakage by the impact from the outside etc.
- Since the spring is being used for this product in a transparent tube, the postures when attaching are freedom, such as facing up, facing down, and sideways.
- A maximum of  $80^{\circ}$ C of oil heat resistant products can be used.
- Standard pressure resistance : 1MPa

## MKCT TYPE

Туре		Dimension (mm)			Maximum flow rate (L/min)
			length	width	Oil
Threaded Type	MKCT20-1TL	Rc1/8	80	30	5
	MKCT20-2TL	Rc1/4	80	30	5
	MKCT20-3TL	Rc3/8	86	30	5
	MKCT30-2TL	Rc1/4	104	43	10
	MKCT30-3TL	Rc3/8	104	43	10
	MKCT30-4TL	Rc1/2	110	43	10
	MKCT35-4TL	Rc1/2	145	50	25
	MKCT35-6TL	Rc3/4	145	50	25
	MKCT45-6TL	Rc3/4	172	62	50
	MKCT45-8TL	Rc1	172	62	50

No.	Name	Material	
01	Transparent tube	Acrylic resin	
02	Joint	Brass	
03	Ball	Nylon	
04	Spring	SUS 304	
05	Frame	Bronze	
06	O ring	Nitrile rubber	

